

# ARMSTRONG - STEAM & ENGINEERING

FROM CONCEPT TO CONCLUSION

## PRODUCT DATA SHEET

PRODUCT # SEP-067

ISSUED 12/99

### DESCRIPTION

BRONZE QUICK ACTING GATE VALVE, SCREWED BSP.  
LEVER OPERATED, CAN BE FITTED WITH OPTIONAL SPRING RETURN LEVER.

COLD WORKING PRESSURE : 1400 KPA

SATURATED STEAM PRESSURE : 900 KPA

MAX TEMPERATURE :

260 DEG C



- A = FACE TO FACE
- B = CENTRE TO TOP
- C = LENGTH OF LEVER
- D = CENTRE TO END OF LEVER
- KG = WEIGHT

SIZE	A	B	C	D	KG	PART NAME	MATERIAL
15	54	56	94	122	.75		
20	56	56	94	122	.76	BODY	BRONZE
25	62	62	114	140	.98	BONNET	BRONZE
32	72	72	130	145	1.4	SPINDLE	BRASS
40	74	82	150	170	2.0	DISC	BRONZE
50	84	96	170	205	2.9	PACKING	PTFE
65	94	110	215	240	4.6	LEVER	CAST
80	100	130	240	258	5.9		
100	112	168	315	390	10.9		

ALL DIMENSIONS ARE IN MM AND ARE APPROXIMATE ONLY IF CRITICAL PLEASE CONFIRM