

ARMSTRONG - STEAM & ENGINEERING

FROM CONCEPT TO CONCLUSION

PRODUCT DATA SHEET

PRODUCT # SEP-300C-300 (CARBON STEEL) / SEP-300A-300 (316 STAINLESS STEEL) ISSUED 7/97

DESCRIPTION


“Y” STRAINER WITH FLANGED ENDS TO ANSI 300# RF.
 SCREENS TO SUIT YOUR APPLICATION. FINE MESH TO 37 MICRON.
 CAN BE SUPPLIED WITH BLOWDOWN CONNECTIONS.
 ANSI 150 AND ANSI 600 CONNECTIONS ARE ALSO AVAILABLE.

COLD WORKING PRESSURE : 5380 KPA

SATURATED STEAM PRESSURE : 2100 KPA

MAX TEMPERATURE :

454 DEG C



SIZE	A	B	BD	CV	KG	PART #	PART NAME	MATERIAL	OPTIONAL
15	156	90	OPT.		4				
20	197	95	OPT.		6				
25	200	95	OPT.		7	1	BODY	WCB - A216	CF8M-316
40	210	95	OPT.		8	2	CAP	WCB - A216	CF8M-316
50	229	160	1/2"		13	3	SCREEN	304	316
65	271	190	1"		23	4	STUD	B7	304 / 316
80	320	228	1-1/4"		25	5	NUT	2H	304 / 316
100	372	273	1-1/2"		30	6	GASKET	NON ASBES.	PTFE
125	460	350	2"		62				
150	502	400	2"		76				
200	635	420	2"		113				
250	740	480	2"		170				
300	860	584	2"		240				

ALL DIMENSIONS ARE IN MM AND ARE APPROXIMATE ONLY IF CRITICAL PLEASE CONFIRM