

This document is located at

[www.armstrongsteam.com.au/sds/300d.pdf](http://www.armstrongsteam.com.au/sds/300d.pdf)

**PRODUCT DATA SHEET**

PRODUCT # SEP-300D


ISSUED 2/99

**DESCRIPTION**

CAST IRON 'Y' TYPE STRAINER. CAN BE SUPPLIED NYLON (FBE) COATED.  
 304 STAINLESS STEEL PERFORATED SCREEN.  
 BOLTED COVER WITH PROVISION FOR BLOWDOWN.  
 SPECIAL SCREENS ARE AVAILABLE TO 37 MICRON.

**COLD WORKING PRESSURE :** 1400 KPA  
**SATURATED STEAM PRESSURE :** NOT RECCOMENDED

**MAX TEMPERATURE :**  
 120 DEG.C.



withdrawal  
 distance

SIZE	A	B	C	CV	KG	PART NAME	MATERIAL	OPTIONAL
25	156	86	50		3			
32	190	108	85		3.5	BODY	CAST IRON	
40	192	108	90		4	COVER	CAST IRON	
50	220	130	100		8	PLUG	MAL IRON	
65	270	180	100		10	SCREEN	304	316
80	290	202	104		15	BOLT	STEEL	
100	350	240	135		21			
125	390	260	175		28			
150	440	320	232		40			
200	540	380	286		75			
250	660	480	320		140			
300	720	600	385		170			

Strainers below  
 50mm have  
 screwed cover,  
 without blowdown  
 connection

ALL DIMENSIONS ARE IN MM AND ARE APPROXIMATE ONLY IF CRITICAL PLEASE CONFIRM